

PE-UHMW - Rundstab

Extrudiert, Dichte 0,93 g/cm³

Lieferlängen:

bis Ø 50 mm 1'000 mm / 2'000 mm / 3'000 mm

bis Ø 180 mm 1'000 mm / 2'000 mm

Ø	Toleranz	Farbe	kg/m	Art.-Nr.	
10	+0.2/+1.0	natur *	0.010	105101	*
15	+0.2/+1.0	natur *	0.010	106044	*
20	+0.5/+1.5	natur	0.326	106045	
25	+0.5/+1.5	natur	0.494	106046	
30	+0.5/+1.5	natur	0.720	106047	
35	+0.5/+2.0	natur	0.995	183929	
40	+0.5/+2.0	natur	1.280	106048	
45	+0.5/+2.0	natur	1.570	183930	
50	+0.5/+2.5	natur	2.030	106049	
60	+0.5/+2.5	natur	2.870	106050	
70	+0.5/+2.5	natur	3.720	106051	
80	+0.5/+3.5	natur	5.100	106052	
90	+0.5/+3.5	natur	6.090	106735	
100	+1.0/+3.5	natur	7.820	106053	
110	+1.0/+3.5	natur	9.420	106054	
120	+1.0/+4.0	natur *	10.740	106055	*
125	+1.0/+4.0	natur	12.000	183931	
140	+1.5/+5.0	natur	15.350	183932	
150	+1.5/+5.0	natur *	16.780	106058	*
160	+1.5/+5.0	natur	19.800	106771	
180	+5.0/+10.0	natur *	26.250	169674	*

Die mit * bezeichneten Abmessungen sind auf Anfrage lieferbar.