

# Nylatron GS

## PA 66 + MoS<sub>2</sub> - Rohr

Extrudiert, Dichte 1,15 g/cm<sup>3</sup>

Lieferlängen: 1'000 mm / 3'000 mm

Ø/mm	Farbe	kg/m	Art.-Nr.
20/10	anthrazit *	0.325	105085 *
25/15	anthrazit	0.433	121556
30/15	anthrazit	0.695	170688
30/20	anthrazit	0.540	163383
36/20	anthrazit	0.980	121557
36/25	anthrazit	0.790	105095
40/25	anthrazit	1.080	105098
40/30	anthrazit	0.840	170689
45/25	anthrazit *	1.480	170690 *
45/30	anthrazit	1.250	106814
45/35	anthrazit	0.960	106812
50/30	anthrazit *	1.700	148990 *
50/35	anthrazit *	1.410	170691 *
50/40	anthrazit *	1.080	170692 *
60/45	anthrazit *	1.830	105103 *
60/50	anthrazit *	1.410	170693 *
65/50	anthrazit *	2.060	170694 *
65/55	anthrazit *	1.600	106868 *
66/53	anthrazit	1.920	105105

A-Ø in mm	Toleranzen in mm	
	A-Ø	I-Ø
Ω <sub>30</sub>	+0.4/+1.1	-0.4/-1.1
Ω <sub>50</sub>	+0.6/+2.0	-0.6/-2.0
Ω <sub>60</sub>	+0.8/+2.5	-0.8/-2.5
Ω <sub>66</sub>	+0.8/+3.0	-0.8/-3.0

Die mit \* bezeichneten Abmessungen sind auf Anfrage lieferbar.