

Nylatron NSM PA 6 G + Festschmierstoff Rundstab

Gegossen, Dichte 1.14 g/cm³

Lieferlängen:

bis Ø 150 mm 1'000 mm / 3'000 mm
ab Ø 160 mm 1'000 mm
ab Ø 210 mm 500 mm / 1'000 mm

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
50	+0.5/+1.5	grau	2.360	105454
56	+0.5/+1.5	grau *	2.950	170269 *
60	+0.5/+1.8	grau	3.400	105455
65	+0.5/+1.8	grau *	3.980	152913 *
70	+0.5/+1.8	grau	4.600	105456
75	+0.7/+2.7	grau	5.320	105462
80	+0.7/+2.7	grau	6.040	105457
85	+1.0/+2.7	grau *	6.850	170270 *
90	+1.0/+2.7	grau	7.670	105458
95	+1.0/+2.9	grau *	8.540	170271 *
100	+1.0/+2.9	grau	9.450	105459
110	+1.0/+3.3	grau	11.450	170273
120	+1.1/+3.8	grau *	13.650	105460 *
125	+1.1/+3.8	grau	14.750	170275
130	+1.2/+4.1	grau	16.000	170276
140	+1.2/+4.1	grau *	18.500	170278 *
150	+1.3/+4.5	grau	21.250	105461
160	+2.0/+7.0	grau *	24.600	170281 *
170	+2.0/+7.0	grau	27.650	105463
180	+2.0/+7.0	grau *	30.950	170282 *
190	+2.0/+7.0	grau	34.400	170283
200	+2.0/+7.0	grau	38.000	170284
210	+3.0/+9.0	grau *	42.400	170285 *
220	+3.0/+9.0	grau	46.400	148637
230	+3.0/+9.0	grau *	50.600	170286 *
240	+3.0/+9.0	grau *	55.000	170287 *
250	+3.0/+9.0	grau *	59.550	170288 *
260	+3.0/+9.0	grau *	64.300	170289 *
270	+3.0/+9.0	grau *	69.250	170290 *
280	+3.0/+9.0	grau *	74.350	170291 *
290	+3.0/+9.0	grau	79.600	170292
300	+3.0/+9.0	grau	85.100	170293
325	+4.0/+11.0	grau *	100.500	170372 *
350	+4.0/+11.0	grau *	116.100	170373 *
375	+4.0/+11.0	grau *	133.000	170374 *

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
400	+4.0/+11.0	grau *	150.900	170375 *
425	+5.0/+13.0	grau *	171.200	170376 *
450	+5.0/+13.0	grau *	191.500	170377 *
475	+5.0/+13.0	grau *	212.900	170378 *
500	+5.0/+13.0	grau *	235.400	170379 *

Die mit * bezeichneten Abmessungen sind auf Anfrage lieferbar.