

Nylatron NSM PA 6 G + Festschmierstoff Platte

Gegossen, Dichte 1.14 g/cm³

Format: 1'220 mm x 2'000 mm

Dicke	Toleranz	Farbe	kg/m ²	Art.-Nr.
10	+0.5/+2.5	grau	13.400	105469
12	+0.5/+2.5	grau	15.738	105464
16	+0.5/+2.5	grau	20.389	105380
20	+0.5/+2.5	grau	25.041	105465
25	+0.5/+2.5	grau	30.881	105466
30	+0.5/+3.0	grau	37.152	106870
35	+0.5/+3.0	grau	42.992	170492
40	+0.5/+3.0	grau	48.811	105468
45	+0.5/+3.0	grau *	54.631	170493 *
50	+0.5/+3.0	grau	60.451	170494
55	+0.5/+3.5	grau *	67.008	170495 *
60	+0.5/+3.5	grau	72.828	170496
65	+0.5/+3.5	grau *	78.689	170497 *
70	+0.5/+4.5	grau *	84.508	106783 *
75	+0.5/+4.5	grau *	90.328	170498 *
80	+0.5/+4.5	grau	96.148	105275
90	+0.5/+4.5	grau *	107.828	170499 *
100	+0.5/+4.5	grau	119.467	170500

Die mit * bezeichneten Abmessungen sind auf Anfrage
lieferbar.