

# PA 66 - Platte

Extrudiert, Dichte 1,14 g/cm<sup>3</sup>

Formate:

bis Dicke 6 mm

1'000 mm x 2'000 mm

ab Dicke 8 mm

610 mm x 1'000 mm / 3000 mm

| Dicke | Toleranz  | Farbe     | kg/m <sup>2</sup> | Art.-Nr. |   |
|-------|-----------|-----------|-------------------|----------|---|
| 1.5   | +/-0.15   | natur *   | 1.717             | 159631   | * |
| 2     | +/-0.15   | natur     | 2.350             | 105051   |   |
| 3     | +/-0.2    | natur     | 3.520             | 106682   |   |
| 4     | +/-0.2    | natur     | 4.700             | 105052   |   |
| 5     | +/-0.25   | natur     | 5.870             | 105057   |   |
| 6     | +/-0.3    | natur     | 7.050             | 105053   |   |
| 8     | +0.2/+1.1 | natur     | 10.080            | 105054   |   |
| 8     | +0.2/+1.1 | schwarz * | 10.080            | 170704   | * |
| 10    | +0.2/+1.1 | natur     | 12.443            | 105055   |   |
| 10    | +0.2/+1.1 | schwarz * | 12.443            | 170705   | * |
| 12    | +0.3/+1.5 | natur     | 15.213            | 105056   |   |
| 12    | +0.3/+1.5 | schwarz * | 15.213            | 170706   | * |
| 15    | +0.3/+1.5 | natur     | 18.770            | 105058   |   |
| 15    | +0.3/+1.5 | schwarz * | 18.770            | 170707   | * |
| 16    | +0.3/+1.5 | natur     | 19.920            | 185855   |   |
| 16    | +0.3/+1.5 | schwarz * | 19.920            | 185856   | * |
| 20    | +0.3/+1.5 | natur     | 24.672            | 105059   |   |
| 20    | +0.3/+1.5 | schwarz * | 24.672            | 170708   | * |
| 25    | +0.3/+1.5 | natur     | 30.574            | 105060   |   |
| 25    | +0.3/+1.5 | schwarz * | 30.574            | 162504   | * |
| 30    | +0.5/+2.5 | natur     | 37.131            | 105061   |   |
| 30    | +0.5/+2.5 | schwarz * | 37.131            | 162506   | * |
| 35    | +0.5/+2.5 | natur     | 43.030            | 185857   |   |
| 35    | +0.5/+2.5 | schwarz * | 43.030            | 185858   | * |
| 40    | +0.5/+2.5 | natur     | 48.934            | 105063   |   |
| 40    | +0.5/+2.5 | schwarz * | 48.934            | 170709   | * |
| 45    | +0.5/+2.5 | natur *   | 54.840            | 185859   | * |
| 45    | +0.5/+2.5 | schwarz * | 54.840            | 185860   | * |
| 50    | +0.5/+2.5 | natur     | 60.740            | 105065   |   |
| 50    | +0.5/+2.5 | schwarz * | 60.740            | 170710   | * |
| 60    | +0.5/+5   | natur     | 73.120            | 105062   |   |
| 60    | +0.5/+3.5 | schwarz * | 73.120            | 185861   | * |
| 70    | +0.5/+3.5 | natur *   | 84.920            | 185862   | * |
| 70    | +0.5/+3.5 | schwarz * | 84.920            | 185863   | * |

| Dicke | Toleranz  | Farbe     | kg/m <sup>2</sup> | Art.-Nr. |   |
|-------|-----------|-----------|-------------------|----------|---|
| 80    | +0.5/+5.0 | natur *   | 97.625            | 185864   | * |
| 80    | +0.5/+5.0 | schwarz * | 97.625            | 185865   | * |
| 90    | +0.5/+5.0 | natur *   | 109.430           | 185866   | * |
| 90    | +0.5/+5.0 | schwarz * | 109.430           | 185867   | * |
| 100   | +0.5/+5.0 | natur *   | 121.230           | 186423   | * |
| 100   | +0.5/+5.0 | schwarz * | 121.230           | 185869   | * |

Die mit \* bezeichneten Abmessungen sind auf Anfrage lieferbar.