

POM-C - Rundstab

Extrudiert, Dichte 1,41 g/cm³

Lieferlängen:

1'000 mm / 3'000 mm

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
3	+0.1/+0.3	natur	0.012	134024
4	+0.1/+0.3	natur	0.020	121296
5	+0.1/+0.4	natur	0.032	121182
5	+0.1/+0.4	schwarz	0.032	148889
6	+0.1/+0.4	natur	0.045	105782
6	+0.1/+0.4	schwarz	0.045	105783
8	+0.1/+0.5	natur	0.079	105784
8	+0.1/+0.5	schwarz	0.079	105785
10	+0.1/+0.5	natur	0.121	105787
10	+0.1/+0.5	schwarz	0.121	105788
12	+0.2/+0.7	natur	0.176	105789
12	+0.2/+0.7	schwarz	0.176	105790
14	+0.2/+0.7	natur	0.237	149034
14	+0.2/+0.7	schwarz	0.237	105791
15	+0.2/+0.7	natur	0.271	105792
15	+0.2/+0.7	schwarz	0.271	105793
16	+0.2/+0.7	natur	0.307	105794
16	+0.2/+0.7	schwarz	0.307	105795
18	+0.2/+0.7	natur	0.386	105796
18	+0.2/+0.7	schwarz	0.386	105797
20	+0.2/+0.8	natur	0.465	105798
20	+0.2/+0.8	schwarz	0.465	105799
22	+0.2/+1.0	natur	0.566	105801
22	+0.2/+1.0	schwarz	0.566	105802
25	+0.2/+1.0	natur	0.726	105803
25	+0.2/+1.0	schwarz	0.726	105804
28	+0.2/+1.0	natur	0.906	105806
28	+0.2/+1.0	schwarz	0.906	105807
30	+0.2/+1.0	natur	1.037	105808
30	+0.2/+1.0	schwarz	1.037	105809
32	+0.2/+1.2	natur	1.184	105810
32	+0.2/+1.2	schwarz	1.184	105811
36	+0.2/+1.2	natur	1.492	121896
36	+0.2/+1.2	schwarz	1.492	131845

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
40	+0.2/+1.2	natur	1.834	105814
40	+0.2/+1.2	schwarz	1.834	105815
45	+0.3/+1.3	natur	2.322	105817
45	+0.3/+1.3	schwarz	2.322	105818
50	+0.3/+1.3	natur	2.856	105819
50	+0.3/+1.3	schwarz	2.856	105820
56	+0.3/+1.3	natur	3.571	105821
56	+0.3/+1.3	schwarz	3.571	105822
60	+0.3/+1.6	natur	4.112	105823
60	+0.3/+1.6	schwarz	4.112	105824
65	+0.3/+1.6	natur	4.816	105825
65	+0.3/+1.6	schwarz	4.816	105826
70	+0.3/+1.6	natur	5.740	105827
70	+0.3/+1.6	schwarz	5.740	105828
75	+0.4/+2.0	natur	6.570	105829
75	+0.4/+2.0	schwarz	6.570	105830
80	+0.4/+2.0	natur	7.298	105831
80	+0.4/+2.0	schwarz	7.298	105832
85	+0.5/+2.2	natur	8.250	105833
85	+0.5/+2.2	schwarz	8.250	120848
90	+0.5/+2.2	natur	9.230	105834
90	+0.5/+2.2	schwarz	9.230	105835
95	+0.6/+2.5	natur	10.390	153393
100	+0.6/+2.5	natur	11.490	105836
100	+0.6/+2.5	schwarz	11.490	105837
110	+0.7/+3.0	natur	14.150	105838
110	+0.7/+3.0	schwarz	14.150	105839
120	+0.8/+3.5	natur	16.900	105840
120	+0.8/+3.5	schwarz	16.900	105841
125	+0.8/+3.5	natur	18.300	163247
130	+0.9/+3.8	natur	19.800	105842
130	+0.9/+3.8	schwarz	19.800	105843
135	+0.9/+3.8	natur *	21.350	186350 *
135	+0.9/+3.8	schwarz *	21.350	105844 *

Die mit * bezeichneten Abmessungen sind auf Anfrage lieferbar.

Reg. 3.1a / 2014-11

Cellpack AG

Kunststofftechnik

Anglikerstrasse 99

CH-5612 Villmergen

Telefon +41 56 618 14 28

Telefax +41 56 621 00 21

kunststofftechnik@cellpack.com

CELLPACK
Kunststofftechnik

Fortsetzung
POM-C - Rundstab

POM-C
Rundstab geschliffen h9

Extrudiert, Dichte 1,41 g/cm³

Lieferlängen:

1'000 mm / 3'000 mm

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
140	+0.9/+3.8	natur	22.900	105845
140	+0.9/+3.8	schwarz	22.900	137312
150	+1.0/+4.2	natur	26.350	105846
150	+1.0/+4.2	schwarz	26.350	105781
170	+1.2/+5.0	natur	33.900	105849
170	+1.2/+5.0	schwarz	33.900	186351
180	+1.2/+5.0	natur	37.900	105851
180	+1.2/+5.0	schwarz	37.900	105852
190	+1.3/+5.5	natur	42.300	186352
190	+1.3/+5.5	schwarz *	42.300	186353 *
200	+1.3/+5.5	natur	46.800	105853
200	+1.3/+5.5	schwarz	46.800	106915
210	+1.3/+5.8	natur	51.600	105854
210	+1.3/+5.8	schwarz *	51.600	186354 *
220	+1.3/+5.8	natur	56.500	186355
220	+1.3/+5.8	schwarz	56.500	154486
230	+1.5/+6.2	natur	61.400	106775
250	+1.5/+6.2	natur	72.850	105855
250	+1.5/+6.2	schwarz	72.850	154484
280	+1.6/+6.5	natur	91.150	130843
280	+1.6/+6.5	schwarz	91.150	180252
300	+1.7/+7.0	natur	106.200	147912

Die mit * bezeichneten Abmessungen sind auf Anfrage lieferbar.

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
3	+0.0/-0.025	natur	0.012	151796
4	+0.0/-0.030	natur	0.020	115505
5	+0.0/-0.030	natur	0.028	104534
5	+0.0/-0.030	schwarz	0.028	115311
6	+0.0/-0.030	natur	0.041	104535
6	+0.0/-0.030	schwarz	0.041	104536
8	+0.0/-0.036	natur	0.072	104537
8	+0.0/-0.036	schwarz	0.072	104538
10	+0.0/-0.036	natur	0.113	104540
10	+0.0/-0.036	schwarz	0.113	104541
12	+0.0/-0.043	natur	0.161	104542
12	+0.0/-0.043	schwarz	0.161	104543
14	+0.0/-0.043	natur	0.237	133440
14	+0.0/-0.043	schwarz	0.237	104544
15	+0.0/-0.043	natur	0.250	104545
15	+0.0/-0.043	schwarz	0.250	104546
16	+0.0/-0.043	natur	0.286	104547
16	+0.0/-0.043	schwarz	0.286	104548
18	+0.0/-0.043	natur	0.362	104549
18	+0.0/-0.043	schwarz	0.362	104550
20	+0.0/-0.052	natur	0.451	104551
20	+0.0/-0.052	schwarz	0.451	104552
22	+0.0/-0.052	natur	0.545	104553
22	+0.0/-0.052	schwarz	0.545	104554
25	+0.0/-0.052	natur	0.700	104556
25	+0.0/-0.052	schwarz	0.700	104557
28	+0.0/-0.052	natur	0.872	104558
28	+0.0/-0.052	schwarz	0.872	104559
30	+0.0/-0.052	natur	1.000	104560
30	+0.0/-0.052	schwarz	1.000	104561
32	+0.0/-0.062	natur	1.160	104562
32	+0.0/-0.062	schwarz	1.160	104712
36	+0.0/-0.062	natur	1.380	171522
36	+0.0/-0.062	schwarz	1.380	156206
40	+0.0/-0.062	natur	1.810	104565
40	+0.0/-0.062	schwarz	1.810	104566
45	+0.0/-0.062	natur	2.260	104567
45	+0.0/-0.062	schwarz	2.260	104568
50	+0.0/-0.062	natur	2.790	104569
50	+0.0/-0.062	schwarz	2.790	104570

Reg. 3.1a / 2014-11

Cellpack AG
 Kunststofftechnik
 Anglikerstrasse 99
 CH-5612 Villmergen

Telefon +41 56 618 14 28
 Telefax +41 56 621 00 21
kunststofftechnik@cellpack.com

CELLPACK
 Kunststofftechnik