

Ertalyte TX

PETP + Festschmierstoff

Rohr

Extrudiert, Dichte 1,44 g/cm³

Lieferlängen: 1'000 mm / 3'000 mm

Ø/mm	Farbe	kg/m	Art.-Nr.	
20/12	hellgrau *	0.349	181560	*
25/15	hellgrau	0.530	181561	
30/20	hellgrau	0.660	181562	
40/30	hellgrau *	1.010	181564	*
45/30	hellgrau	1.520	181565	
50/40	hellgrau	1.300	181566	
55/45	hellgrau *	1.530	181567	*
60/30	hellgrau	3.440	181568	
65/50	hellgrau	2.480	181569	
70/40	hellgrau	4.270	181570	
80/50	hellgrau	5.040	181572	
90/50	hellgrau	7.300	181573	
90/70	hellgrau *	4.690	181574	*
100/50	hellgrau	9.530	181575	
100/80	hellgrau	5.280	181576	
115/70	hellgrau	11.000	181577	
125/50	hellgrau	16.400	181578	
140/70	hellgrau	18.500	162537	
160/80	hellgrau	24.250	181579	
180/100	hellgrau	28.300	181580	
180/140	hellgrau *	17.750	181581	*
200/100	hellgrau	37.500	181582	
200/160	hellgrau *	20.350	181583	*

A-Ø in mm	Toleranzen in mm	
	A-Ø	I-Ø
≤ 30	+0.4/+1.1	-0.4/-1.1
≤ 50	+0.6/+2.0	-0.6/-2.0
≤ 60	+0.8/+2.5	-0.8/-2.5
≤ 80	+0.8/+3.0	-0.8/-3.0
≤ 100	+1.2/+3.6	-1.6/-5.0
≤ 140	+1.5/+4.5	-2.0/-6.5
≤ 180	+1.8/+5.4	-2.2/-7.5
≥ 200	+2.0/+6.0	-2.5/-8.5

Die mit * bezeichneten Abmessungen sind auf Anfrage lieferbar.