

# PC - Rundstab

Extrudiert, Dichte 1,20 g/cm<sup>3</sup>

Lieferlängen: 1'000 mm / 3'000 mm

Ø/mm	Toleranz	Farbe	kg/m	Art.-Nr.
6	+0.1/+0.4	transp.	0.037	114119
8	+0.1/+0.5	transp.	0.066	107020
10	+0.1/+0.5	transp.	0.101	107032
12	+0.2/+0.9	transp.	0.151	107437
16	+0.2/+0.9	transp.	0.262	107438
20	+0.2/+0.9	transp.	0.404	168123
25	+0.2/+1.2	transp.	0.630	121685
30	+0.2/+1.2	transp.	0.900	107017
36	+0.2/+1.6	transp.	1.300	172775
40	+0.2/+1.6	transp.	1.600	113274
50	+0.3/+2.0	transp.	2.500	107040
60	+0.3/+2.5	transp.	3.610	152801
70	+0.3/+2.5	transp.	4.880	107441
80	+0.4/+3.0	transp.	6.390	107442
90	+0.5/+3.4	transp.*	8.090	107443 *
100	+0.6/+3.8	transp.	9.990	107436
120	+0.8/+4.6	transp.	14.400	181606
130	+0.9/+5.4	transp.*	16.950	178270 *
150	+1.0/+5.8	transp.	22.500	181608
180	+1.2/+7.4	transp.	32.500	181609
200	+1.3/+8.5	transp.	40.150	181610

Die mit \* bezeichneten Abmessungen sind auf Anfrage lieferbar.