

Cevodur WHA - Rundstab

Gepresst, Dichte 1,36 g/cm³

Lieferlänge: 1'000 mm / 2'000 mm

| Ø/mm | Toleranz | Farbe | kg/m | Art.-Nr. |
|------|-------------|-------|--------|----------|
| 10 | +0.13/-0.13 | braun | 0.110 | 105728 |
| 12 | +0.13/-0.13 | braun | 0.150 | 105729 |
| 15 | +0.13/-0.13 | braun | 0.240 | 105730 |
| 16 | +0.13/-0.13 | braun | 0.270 | 166182 |
| 18 | +0.13/-0.13 | braun | 0.350 | 184221 |
| 20 | +0.13/-0.13 | braun | 0.430 | 116253 |
| 25 | +0.13/-0.13 | braun | 0.690 | 105725 |
| 30 | +0.25/-0.25 | braun | 0.960 | 105724 |
| 35 | +0.25/-0.25 | braun | 1.310 | 105723 |
| 40 | +0.25/-0.25 | braun | 1.710 | 106575 |
| 45 | +0.25/-0.25 | braun | 2.160 | 154318 |
| 50 | +0.40/-0.40 | braun | 2.670 | 106586 |
| 55 | +0.40/-0.40 | braun | 3.230 | 184227 |
| 60 | +0.40/-0.40 | braun | 3.850 | 106587 |
| 65 | +0.40/-0.40 | braun | 4.510 | 184229 |
| 70 | +0.40/-0.40 | braun | 5.230 | 106588 |
| 75 | +0.50/-0.50 | braun | 6.010 | 166140 |
| 80 | +0.50/-0.50 | braun | 6.840 | 105739 |
| 85 | +0.50/-0.50 | braun | 7.720 | 184232 |
| 90 | +0.50/-0.50 | braun | 8.650 | 106590 |
| 95 | +0.50/-0.50 | braun | 9.640 | 184234 |
| 100 | +0.50/-0.50 | braun | 10.680 | 184213 |
| 105 | +0.50/-0.50 | braun | 11.780 | 184214 |
| 110 | +0.50/-0.50 | braun | 12.920 | 184215 |
| 115 | +0.50/-0.50 | braun | 14.130 | 184216 |
| 120 | +0.50/-0.50 | braun | 15.380 | 184217 |
| 125 | +0.50/-0.50 | braun | 16.690 | 184218 |
| 130 | +0.50/-0.50 | braun | 18.050 | 184220 |