

PE-UHMW - Barre ronde

Extrudée, densité de 0,93 g/cm³

Longueurs:

jusqu'au Ø 50 mm 1'000 mm / 2'000 mm / 3'000 mm

à partir de Ø 180 mm 1'000 mm / 2'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.	
10	+0.2/+1.0	nature *	0.010	105101	*
15	+0.2/+1.0	nature *	0.010	106044	*
20	+0.5/+1.5	nature	0.326	106045	
25	+0.5/+1.5	nature	0.494	106046	
30	+0.5/+1.5	nature	0.720	106047	
35	+0.5/+2.0	nature	0.995	183929	
40	+0.5/+2.0	nature	1.280	106048	
45	+0.5/+2.0	nature	1.570	183930	
50	+0.5/+2.5	nature	2.030	106049	
60	+0.5/+2.5	nature	2.870	106050	
70	+0.5/+2.5	nature	3.720	106051	
80	+0.5/+3.5	nature	5.100	106052	
90	+0.5/+3.5	nature	6.090	106735	
100	+1.0/+3.5	nature	7.820	106053	
110	+1.0/+3.5	nature	9.420	106054	
120	+1.0/+4.0	nature *	10.740	106055	*
125	+1.0/+4.0	nature	12.000	183931	
140	+1.5/+5.0	nature	15.350	183932	
150	+1.5/+5.0	nature *	16.780	106058	*
160	+1.5/+5.0	nature	19.800	106771	
180	+5.0/+10.0	nature *	26.250	169674	*

Les dimensions marquées d'un * sont livrables sur demande.