

PE-UHMW ASTL - Barre ronde

Pressée et tournée, densité de 0,95 g/cm³

Longueurs:

jusqu'au Ø 60 mm 1'000 mm / 2'000 mm
à partir de Ø 70 mm 1'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.
20	+0.6/+1.0	noir	0.329	180638
25	+0.6/+1.0	noir	0.505	180639
30	+0.6/+1.0	noir	0.720	180640
35	+0.6/+1.0	noir	0.975	180641
40	+0.6/+1.0	noir	1.270	180642
45	+0.6/+1.0	noir	1.600	180643
50	+0.6/+1.0	noir	1.960	180644
55	+0.6/+1.0	noir	2.370	180645
60	+0.6/+1.0	noir	2.810	180646
70	+1.1/+1.5	noir	3.870	180647
80	+1.1/+1.5	noir	5.030	180648
90	+1.1/+1.5	noir	6.350	180649
100	+1.1/+1.5	noir	7.810	180650
110	+1.8/+2.2	noir	9.550	180651
120	+1.8/+2.2	noir	11.350	180652
130	+1.8/+2.2	noir	13.250	180653
140	+1.8/+2.2	noir	15.350	180654
150	+1.8/+2.2	noir	17.600	180655