

# Nylatron GS

## PA 66 + MoS<sub>2</sub> - Plaque

Extrudée, densité 1,15 g/cm<sup>3</sup>

Formats:

jusqu'à ép. 6.35 mm                      610 mm x 1'220 mm

à partir d'ép. 8 mm                      610 mm x 1'000 / 3'000 mm

ép.	Tolérance	Couleur	kg/m <sup>2</sup>	No. d'art.	
1.59	-0.14/+0.11	anthracite *	1.880	105128	*
2.38	-0.14/+0.11	anthracite *	2.820	105129	*
3.18	-0.14/+0.11	anthracite	3.740	105130	
4.76	-0.01/+0.62	anthracite *	5.910	105131	*
6.35	+0,0/+0.63	anthracite *	7.650	105132	*
8	+0.2/+0.9	anthracite	10.262	121572	
10	+0.2/+0.9	anthracite	12.672	105133	
12	+0.3/+1.5	anthracite	15.475	158670	
16	+0.3/+1.5	anthracite	20.328	105135	
20	+0.3/+1.5	anthracite	25.164	116320	
25	+0.3/+1.5	anthracite	31.148	170695	
30	+0.5/+2.5	anthracite	37.869	170696	
35	+0.5/+2.5	anthracite *	43.852	170698	*
40	+0.5/+2.5	anthracite	49.918	170700	
45	+0.5/+2.5	anthracite *	55.984	170701	*
50	+0.5/+2.5	anthracite	61.967	170702	

Les dimensions marquées d'un \* sont livrables sur demande.