

Nylatron GS PA 66 + MoS₂ - Tube

Extrudé, densité 1,15 g/cm³

Longueurs: 1'000 mm / 3'000 mm

Ø/mm	Couleur	kg/m	No. d'art.	
20/10	anthracite *	0.325	105085	*
25/15	anthracite	0.433	121556	
30/15	anthracite	0.695	170688	
30/20	anthracite	0.540	163383	
36/20	anthracite	0.980	121557	
36/25	anthracite	0.790	105095	
40/25	anthracite	1.080	105098	
40/30	anthracite	0.840	170689	
45/25	anthracite *	1.480	170690	*
45/30	anthracite	1.250	106814	
45/35	anthracite	0.960	106812	
50/30	anthracite *	1.700	148990	*
50/35	anthracite *	1.410	170691	*
50/40	anthracite *	1.080	170692	*
60/45	anthracite *	1.830	105103	*
60/50	anthracite *	1.410	170693	*
65/50	anthracite *	2.060	170694	*
65/55	anthracite *	1.600	106868	*
66/53	anthracite	1.920	105105	

E-Ø en mm	Tolérances en mm	
	E-Ø	I-Ø
⊘ 30	+0.4/+1.1	-0.4/-1.1
⊘ 50	+0.6/+2.0	-0.6/-2.0
⊘ 60	+0.8/+2.5	-0.8/-2.5
⊘ 66	+0.8/+3.0	-0.8/-3.0

Les dimensions marquées d'un * sont livrables sur demande.

Reg. 2.10c / 2014-11

Cellpack AG
Plastics Technology
Anglikerstrasse 99
CH-5612 Villmergen

Telefon +41 56 618 14 28
Telefax +41 56 621 00 21
kunststofftechnik@cellpack.com


Plastics Technology