

Nylatron NSM

PA 6 G + lubrifiant solide

Plaque

Coulée, densité 1.14 g/cm³

Format: 1'220 mm x 2'000 mm

ép.	Tolérance	Couleur	kg/m ²	No. d'art.
10	+0.5/+2.5	gris	13.400	105469
12	+0.5/+2.5	gris	15.738	105464
16	+0.5/+2.5	gris	20.389	105380
20	+0.5/+2.5	gris	25.041	105465
25	+0.5/+2.5	gris	30.881	105466
30	+0.5/+3.0	gris	37.152	106870
35	+0.5/+3.0	gris	42.992	170492
40	+0.5/+3.0	gris	48.811	105468
45	+0.5/+3.0	gris *	54.631	170493 *
50	+0.5/+3.0	gris	60.451	170494
55	+0.5/+3.5	gris *	67.008	170495 *
60	+0.5/+3.5	gris	72.828	170496
65	+0.5/+3.5	gris *	78.689	170497 *
70	+0.5/+4.5	gris *	84.508	106783 *
75	+0.5/+4.5	gris *	90.328	170498 *
80	+0.5/+4.5	gris	96.148	105275
90	+0.5/+4.5	gris *	107.828	170499 *
100	+0.5/+4.5	gris	119.467	170500

Les dimensions marquées d'un * sont livrables sur demande.