

# PA 66 E + 30% GF

## Barre ronde

Extrudée, densité 1,29 g/cm<sup>3</sup>

Longueurs: 1'000 mm / 3'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.
10	+0.1/+0.5	noir	0.111	115495
12	+0.2/+0.7	noir	0.163	170666
15	+0.2/+0.7	noir	0.250	115491
16	+0.2/+0.7	noir	0.283	170667
18	+0.2/+0.7	noir	0.355	170668
20	+0.2/+0.7	noir	0.436	120211
22	+0.2/+0.9	noir*	0.530	170669 *
25	+0.2/+0.9	noir	0.680	120213
28	+0.2/+0.9	noir *	0.850	170670 *
30	+0.2/+0.9	noir	0.970	148074
32	+0.2/+1.1	noir *	1.110	170671 *
36	+0.2/+1.1	noir	1.400	120299
40	+0.2/+1.1	noir	1.720	107459
45	+0.3/+1.3	noir	2.180	170672
50	+0.3/+1.3	noir	2.680	132483
60	+0.3/+1.6	noir	3.860	118254
70	+0.3/+1.6	noir	5.220	170673
80	+0.4/+2.0	noir	6.840	170674
90	+0.5/+2.2	noir *	8.660	170675 *
100	+0.6/+2.5	noir	10.700	138720
110	+0.7/+3.0	noir *	13.000	170676 *
120	+0.8/+3.5	noir	15.500	170677
125	+0.8/+3.5	noir *	16.800	170678 *
130	+0.9/+3.8	noir	18.200	170679
140	+0.9/+3.8	noir *	21.050	170680 *
150	+1.0/+4.2	noir	24.200	170681
180	+1.2/+5.0	noir	34.850	170682
200	+1.3/+5.5	noir	42.950	170683

Les dimensions marquées d'un \* sont livrables sur demande.