

PA 66 - Tube

Extrudé, densité 1,14 g/cm³

Longueurs: 1'000 mm / 3'000 mm

Ø/mm	Couleur	kg/m	No. d'art.	
20/10	nature *	0.314	153936	*
20/15	nature *	0.207	170793	*
22/10	nature *	0.393	170794	*
25/12	nature	0.488	155352	
25/15	nature *	0.418	170795	*
25/18	nature *	0.332	170796	*
28/12	nature *	0.635	170797	*
28/20	nature *	0.414	170798	*
30/15	nature	0.675	149060	
30/20	nature *	0.525	170799	*
32/15	nature *	0.835	170800	*
32/20	nature	0.690	160291	
32/25	nature *	0.497	170801	*
36/17	nature *	1.040	170802	*
36/25	nature *	0.755	170803	*
40/20	nature *	1.230	170804	*
40/25	nature	1.040	170805	
40/30	nature *	0.800	170806	*
45/25	nature *	1.440	170807	*
45/30	nature *	1.200	170808	*
45/35	nature	0.915	170809	
50/30	nature	1.640	170810	
50/40	nature	1.030	170811	
55/35	nature *	1.910	170812	*
60/40	nature	2.120	151818	
70/50	nature	2.600	170817	
80/60	nature *	3.030	170819	*
100/80	nature	4.180	170825	

E-Ø en mm	Tolérances en mm	
	E-Ø	I-Ø
≤ 30	+0.4/+1.1	-0.4/-1.1
≤ 50	+0.6/+2.0	-0.6/-2.0
≤ 60	+0.8/+2.5	-0.8/-2.5
≤ 80	+0.8/+3.0	-0.8/-3.0
≤ 100	+1.2/+3.6	-1.6/-5.0

Les dimensions marquées d'un * sont livrables sur demande.