

PA 12 E - Plaque

Extrudée, densité 1,02 g/cm³

Formats:

jusqu'à ép. 6 mm 1'000 mm x 2'000 mm

à partir d'ép. 8 mm 500 mm x 1'000 / 2'000 mm

ép.	Tolérance	Couleur	kg/m ²	No. d'art.	
1	+/-0.1	nature *	1.070	170758	*
2	+/-0.15	nature	2.120	170759	
3	+/-0.2	nature	3.156	170760	
4	+/-0.2	nature	4.240	170761	
5	+/-0.25	nature	5.310	170762	
6	+/-0.3	nature	6.370	170763	
8	+0.2/+1.1	nature	9.400	170764	
8	+0.2/+1.1	noir *	9.400	170765	*
10	+0.2/+1.1	nature	11.200	170766	
10	+0.2/+1.1	noir *	11.200	170767	*
12	+0.3/+1.5	nature	13.400	170768	
12	+0.3/+1.5	noir *	13.400	170769	*
15	+0.3/+1.5	nature	17.400	136430	
15	+0.3/+1.5	noir *	17.400	170770	*
20	+0.3/+1.5	nature	21.800	170771	
20	+0.3/+1.5	noir *	21.800	170772	*
25	+0.3/+1.5	nature	27.000	138733	
25	+0.3/+1.5	noir *	27.000	170773	*
30	+0.5/+2.5	nature	33.400	141920	
30	+0.5/+2.5	noir *	33.400	170774	*
40	+0.5/+2.5	nature	42.800	141921	
40	+0.5/+2.5	noir *	42.800	170775	*
50	+0.5/+2.5	nature	53.800	138734	
50	+0.5/+2.5	noir *	53.800	170776	*

Les dimensions marquées d'un * sont livrables sur demande.