

PMMA coulé - Barre ronde

Coulée, densité 1,19 g/cm³

Longueurs: 1'000 mm / 2'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.
2	+/-0.15	transp.	0.004	181614
3	+/-0.15	transp.	0.009	181615
4	+/-0.15	transp.	0.016	181616
5	+/-0.15	transp.	0.024	181617
6	+/-0.15	transp.	0.040	107398
7	+/-0.15	transp.	0.047	181618
8	+/-0.15	transp.	0.060	107044
10	+/-0.15	transp.	0.100	113271
12	+/-0.15	transp.	0.140	107024
15	+/-0.15	transp.	0.220	157457
16	+/-0.15	transp.	0.250	181619
18	+/-0.15	transp.	0.310	181620
20	+/-0.15	transp.	0.380	149572
22	+/-0.15	transp.	0.460	158790
25	+/-0.15	transp.	0.590	141590
26	+/-0.15	transp.	0.640	181621
28	+/-0.15	transp.	0.740	181622
30	+/-0.15	transp.	0.850	158792
35	+/-0.30	transp.	1.160	157458
40	+/-0.30	transp.	1.510	179405
45	+/-0.30	transp.	1.910	181624
50	+/-0.30	transp.	2.360	107397
60	+/-0.15	transp.	3.400	158024
65	+/-0.30	transp.	4.000	168750
70	+/-0.50	transp.	4.620	181625
80	+/-0.50	transp.	6.030	181626
90	+/-0.50	transp.	7.640	181627
100	+/-0.50	transp.	9.420	177749
140	+/-0.50	transp.	18.500	151270
150	+/-0.50	transp.	21.200	181628

Le PMMA extrudé sous forme de barre ronde et de plaque est livrable sur demande.

Les dimensions marquées d'un * sont livrables sur demande.