

# Formatron CTF

## POM-C+PTFE - Barre ronde

Extrudée, densité 1,52 g/cm<sup>3</sup>

Longueurs: 1'000 mm / 3'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.	
6	+0.1/+0.4	nature *	0.060	181504	*
8	+0.1/+0.5	nature *	0.090	181505	*
10	+0.1/+0.5	nature *	0.140	105924	*
12	+0.2/+0.7	nature *	0.180	105925	*
15	+0.2/+0.7	nature *	0.290	181506	*
16	+0.2/+0.7	nature *	0.330	105930	*
18	+0.2/+0.7	nature *	0.420	181507	*
20	+0.2/+0.7	nature *	0.510	105926	*
22	+0.2/+0.9	nature *	0.610	181508	*
25	+0.2/+0.9	nature *	0.800	105928	*
28	+0.2/+0.9	nature *	1.000	181509	*
30	+0.2/+0.9	nature *	1.150	106689	*
32	+0.2/+1.1	nature *	1.300	181510	*
36	+0.2/+1.1	nature *	1.600	181511	*
40	+0.2/+1.1	nature *	2.100	105747	*
45	+0.3/+1.3	nature *	2.650	105931	*
50	+0.3/+1.3	nature *	3.150	105932	*
55	+0.3/+1.3	nature *	3.650	105933	*
60	+0.3/+1.6	nature *	4.400	105934	*
65	+0.3/+1.6	nature *	5.150	105935	*
70	+0.3/+1.6	nature *	5.750	181512	*
80	+0.4/+2.0	nature *	7.500	106902	*
90	+0.5/+2.2	nature *	9.500	181513	*
100	+0.6/+2.5	nature *	11.800	167804	*
110	+0.6/+3.0	nature *	14.200	113240	*
125	+0.8/+3.5	nature *	18.400	181514	*

Les dimensions marquées d'un \* sont livrables sur demande.