

# Ertalyte TX

## PETP + lubrifiant solide

### Barre ronde

Extrudée, densité 1,44 g/cm<sup>3</sup>

Longueurs:

jusqu'au Ø 100 mm 1'000 mm / 3'000 mm

à partir de Ø 110 mm 1'000 mm

Ø/mm	Tolérance	Couleur	kg/m	No. d'art.
10	+0.1/+0.5	gris clair	0.122	166490
12	+0.2/+0.7	gris clair	0.178	166491
16	+0.2/+0.7	gris clair	0.311	118320
20	+0.2/+0.7	gris clair	0.480	160259
25	+0.2/+0.9	gris clair	0.750	118321
30	+0.2/+0.9	gris clair	1.070	174650
36	+0.2/+1.1	gris clair	1.540	181534
40	+0.2/+1.1	gris clair	1.900	132630
45	+0.3/+1.3	gris clair	2.410	181535
50	+0.3/+1.3	gris clair	2.960	181536
60	+0.3/+1.6	gris clair	4.260	139167
70	+0.3/+1.6	gris clair	5.780	149417
80	+0.4/+2.0	gris clair	7.570	181537
90	+0.5/+2.2	gris clair	9.580	181538
100	+0.6/+2.5	gris clair	11.850	181539
110	+0.7/+3.0	gris clair	14.350	181540
120	+0.8/+3.5	gris clair	17.150	181541
130	+0.9/+3.8	gris clair	20.100	181542
150	+1.0/+4.2	gris clair	26.750	181543
170	+1.2/+5.0	gris clair *	34.400	177983 *

Les dimensions marquées d'un \* sont livrables sur demande.