

Ertalyte TX

PETP + lubrifiant solide

Tube

Extrudé, densité 1,44 g/cm³

Longueurs: 1'000 mm / 3'000 mm

Ø/mm	Couleur	kg/m	No. d'art.	
20/12	gris clair *	0.349	181560	*
25/15	gris clair	0.530	181561	
30/20	gris clair	0.660	181562	
40/30	gris clair *	1.010	181564	*
45/30	gris clair	1.520	181565	
50/40	gris clair	1.300	181566	
55/45	gris clair *	1.530	181567	*
60/30	gris clair	3.440	181568	
65/50	gris clair	2.480	181569	
70/40	gris clair	4.270	181570	
80/50	gris clair	5.040	181572	
90/50	gris clair	7.300	181573	
90/70	gris clair *	4.690	181574	*
100/50	gris clair	9.530	181575	
100/80	gris clair	5.280	181576	
115/70	gris clair	11.000	181577	
125/50	gris clair	16.400	181578	
140/70	gris clair	18.500	162537	
160/80	gris clair	24.250	181579	
180/100	gris clair	28.300	181580	
180/140	gris clair *	17.750	181581	*
200/100	gris clair	37.500	181582	
200/160	gris clair *	20.350	181583	*

E-Ø en mm	Tolérances en mm	
	E-Ø	I-Ø
⊘ 30	+0.4/+1.1	-0.4/-1.1
⊘ 50	+0.6/+2.0	-0.6/-2.0
⊘ 60	+0.8/+2.5	-0.8/-2.5
⊘ 80	+0.8/+3.0	-0.8/-3.0
⊘ 100	+1.2/+3.6	-1.6/-5.0
⊘ 140	+1.5/+4.5	-2.0/-6.5
⊘ 180	+1.8/+5.4	-2.2/-7.5
⊘ 200	+2.0/+6.0	-2.5/-8.5

Les dimensions marquées d'un * sont livrables sur demande.